

● PRINTER RUSH ●  
(PTO ASSISTANCE)

Application :	<u>09452802</u>	Examiner :	<u>Bayard</u>	GAU :	<u>2631</u>
From:	<u>clwc</u>	Location:	<u>IDC</u> <u>FMF</u> <u>FDC</u>	Date:	<u>7-22-05</u>
Tracking #: <u>epin 09452802</u> Week Date: <u>05-16-05</u>					

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input type="checkbox"/> DRW	_____	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input checked="" type="checkbox"/> SPEC	<u>5-06-05</u>	

[RUSH] MESSAGE:

There are two tables labeled "Table 1"  
page 8 and page 16

Thank you

[XRUSH] RESPONSE:

Corrected.

INITIALS: SBH

NOTE: This form will be included as part of the official USPTO record, with the Response document coded as XRUSH.

REV 10/04

2/  
Table 1. Link State History Table of Goodness Counters

	$f_1$	$f_2$	$f_3$	$f_{78}$	$f_{79}$
5	SLAVE 1	GC(1,1)	GC(1,2)	GC(1,3)	—
	SLAVE 2	GC(2,1)	GC(2,2)	GC(2,3)	—
	SLAVE 3	GC(3,1)	GC(3,2)	GC(3,3)	—
	SLAVE 4	GC(4,1)	GC(4,2)	GC(4,3)	—
	SLAVE 5	GC(5,1)	GC(5,2)	GC(5,3)	—
	SLAVE 6	GC(6,1)	GC(6,2)	GC(6,3)	—
	SLAVE 7	GC(7,1)	GC(7,2)	GC(7,3)	—
10					
As the number of bits in the counter is to be limited to minimize the overhead in transmitting the information to the master, the counters $GC(i,j)$ are allowed to count up to the maximum value and stay there until reset. The value of any counter $GC(i,j)$ received by the master indicates the relative goodness of the link between the master and slave "i" on the frequency $f_j$ ; the higher the count value, the better the link. In this method, as the slaves listen to all the master transmissions and record the successful transmissions, the monitoring of interference on different frequencies occurs more frequently, and therefore results in better characterization of the link states.					
15					
10					
20					
25					
30					
35					
40					
45					
50					
55					
60					
65					
70					
75					
80					
85					
90					
95					
100					
105					
110					
115					
120					
125					
130					
135					
140					
145					
150					
155					
160					
165					
170					
175					
180					
185					
190					
195					
200					
205					
210					
215					
220					
225					
230					
235					
240					
245					
250					
255					
260					
265					
270					
275					
280					
285					
290					
295					
300					
305					
310					
315					
320					
325					
330					
335					
340					
345					
350					
355					
360					
365					
370					
375					
380					
385					
390					
395					
400					
405					
410					
415					
420					
425					
430					
435					
440					
445					
450					
455					
460					
465					
470					
475					
480					
485					
490					
495					
500					
505					
510					
515					
520					
525					
530					
535					
540					
545					
550					
555					
560					
565					
570					
575					
580					
585					
590					
595					
600					
605					
610					
615					
620					
625					
630					
635					
640					
645					
650					
655					
660					
665					
670					
675					
680					
685					
690					
695					
700					
705					
710					
715					
720					
725					
730					
735					
740					
745					
750					
755					
760					
765					
770					
775					
780					
785					
790					
795					
800					
805					
810					
815					
820					
825					
830					
835					
840					